



PERFECT SCORE TECHNOLOGIES

4012 Bronze Way
 Phone (214) 331-0002
 Email: info@pstmfg.com

Dallas, Texas 75237
 Fax (214) 331-0013
 Web: http://www.pstmfg.com

Industrial Dust Collector

Model: DC-3 & DC-3H

Model	3 HP DUST COLLECTOR	
	Description	Price
DC-3	3HP Dust Collector	5400.00
DC-3H	3HP Dust Collector w/HEPA Unit	5700.00
Replacement Parts		
HF030-03	0.3 Micron HEPA Filter	51.00
HF100-1	1 Micron HEPA Filter	90.00
DCIQ-F	DC-3 / DC-3H Filter bag	115.00
DC-HOSE	4" Duct Hose (Sold by Lineal Foot)	19.50 Per LF



DC-3H Filter Unit

Selection Overview	Model DC-3	Model DC-3H
Low E Rated (< 0.5 micron filters)	No - Stock filters limited to 3.0 microns	Yes - filters to 0.3 microns
General glass fabrication / edging	Yes	Yes
Blower Horsepower	3 Horsepower	
Electrical Requirements	230v / 8A , optional 460 / 4A	
Inlet Ports - dual 4" dia ports	Capable of servicing two twin seamers within adjacent area	
Heavy Duty Flex Hose	Includes 1 @ 12'L - Additional hose sold separately	
Internal Filter Type	16 units - filter mesh cloth bags - 3 micron	
Bag Cleaning Method	Built-in bag shaker mechanism with catch basin door for easy cleaning	
HEPA Exhaust Filtering	None , cannot be added	6 cartridge unit - 0.3 microns
HEPA Cleaning Method		Cleaning limited, replacement typ.
Foot Print	26" wide x 20" deep x 70" height	26" wide x 29" deep x 70" height
Shipping Dims	Weight 561lbs Dimensions 48 x 48 x 81	

SAFETY WARNING

Users employing glass grinding / sanding equipment should review the dust collection filtering requirements per glass manufactures safety data sheet. The grinding / sanding of Low E coated glass requires dust particulate collection of 0.5 microns or less. PST dust collector Model DC-3H provides a post filtering HEPA unit for Low E applications.